



## Fire Alarm Panel

### Product Overview

The SIRIUS series of alarm systems are the latest generation of security product designed specifically keeping in mind the growing need of instant notification and remote monitoring and health monitoring of security device.

### Features

- Fully Confirm IS 2189
- Zone Wise Fire Fault LED indication
- Zone Wise Isolation Facility
- Auto Dialer Optional
- Mains on, system on, charger on, visual indications. Potential Free Contact Facility
- External s/w for reset, silence, lamp test
- External s/w to test each zone fire, open, short status manually
- Inbuilt Buzzer 16x2 line LCD display
- Inbuilt Battery charger & Battery space Operates on 230 V 50 Hz AC

### Technical Specification

|                              |                                |
|------------------------------|--------------------------------|
| <b>Power I/P</b>             | 230VAC/24 VDC                  |
| <b>Power consumption</b>     | 30 watt/200 watt (Normal/fire) |
| <b>End of Line</b>           | 4K7                            |
| <b>No of zones</b>           | 2 or 4                         |
| <b>Detection O/P supply</b>  | 24 V DC                        |
| <b>Hooter O/P supply</b>     | 24 V DC                        |
| <b>Operating temperature</b> | 10 °C to 40 °C                 |

|                           |                        |
|---------------------------|------------------------|
| <b>Cabinet Type</b>       | MS                     |
| <b>Colour</b>             | Off White              |
| <b>Paint</b>              | Powder Coating         |
| <b>Knock Out</b>          | ZO mm                  |
| <b>Dimension</b>          | 310x95x230mm           |
| <b>Weight</b>             | 4.2 kg without battery |
| <b>Operating Humidity</b> | 95% (Non-condensing)   |